



		Tires		Clutch settings		Front shocks		Engine		
Date/Track	DM Türkheim	Front shore	left 32 / right 32	Shoe / Bell	Alu Cap	Piston	1 standard	Type	Picco torque	
Driver	Robert Pietsch	Rear shore	left 35 / right 35	Bell clearance (mm)	0,6	Oil	600	Plug/Fuel	Plug P7TC / Fuel Maxima	
Temp. °C.	air / track	Front Ø	left 69 / right 69	Spring/adj. Nut(mm)	kit / 0,5mm	Spring	yellow	Pipe/Manifold	Pipe 2033 / Manifold short	
		Rear Ø	left 76 / right 76	Bell axial play (mm)	0,1-0,2		Rear shocks		Gear ratio chart	
Track layout/traction	technical <input type="radio"/> low <input type="radio"/>	Body			Gearing		Piston	2 standard		
	mixed <input checked="" type="radio"/> medium <input checked="" type="radio"/>	Type	PFR18		1st gear	16 / 50		Oil	700	
	fast <input type="radio"/> high <input type="radio"/>	Wing position (mm)	8		2n gear	19 / 46		Spring	grey	
									1st	48 49 50
									1st	16 7,2 7,35 7,5
									1st	17 6,776 6,918 7,059
									2nd	19 5,684 5,811 5,937
									2nd	20 5,4 5,52 5,64
									2nd	21 5,143 5,257 5,371

