



		Tires		Clutch settings		Front shocks		Engine						
Date/Track	6/1/2014 Japan Nats Hokusei Circuit	Front shore	left ZAC 30° / right ZAC 30°	Shoe / Bell	Black (H2709) / Al. Bell (H2708)	Piston	1.3x1	Type	O.S Speed R2101					
Driver	Takaaki Shimo	Rear shore	left ZAC 35° / right ZAC 35°	Bell clearance (mm)	0.6	Oil	600	Plug/ Fuel	Plug RP7 / Fuel COSMO					
Temp. °C.	air / track	Front Ø	left 70 / right 70	Spring/adj. Nut(mm)	H2706 / 0	Spring	Yellow (H0515)	Pipe/ Manifold	Pipe EFRA2098 / Manifold					
		Rear Ø	left 76 / right 76	Bell axial play (mm)	0.2		Rear shocks	Gear ratio chart						
Track layout/ traction	technical <input type="radio"/> low <input type="radio"/>	Body		Gearing		Piston	1.1x2	1st		2nd				
	mixed <input checked="" type="radio"/> medium <input checked="" type="radio"/>	Type	BLITZ TS030	1st gear	16 / 50	Oil	600	16	7,2	7,35	7,5			
	fast <input type="radio"/> high <input type="radio"/>	Wing position (mm)		2n gear	20 / 46	Spring	Pink (Serpent)	17	6,776	6,918	7,059			
								19				5,684	5,811	5,937
								20				5,4	5,52	5,64
								21				5,143	5,257	5,371

