



		Tires		Clutch settings		Front shocks		Engine							
Date/Track	Hokusei Circuit	Front shore	left ZAC ZBB-812CSH (C)	right ZAC ZBB-812CSH (C)	Shoe	Yellow	Piston	Φ1.3x1	Type	OS 12XZ Speed Spec III					
Driver	Takaaki Shimo	Rear shore	left ZAC ZBB-9121SH (37)	right ZAC ZBB-9121SH (37)	Bell clearance (mm)	0.5	Oil	#600	Plug/Fuel	Plug RP6	Fuel COSMO				
Temp. °C.	air / track	Front φ	left 64	right 64	Spring	Hard	Spring	Xray Progressive	Pipe/Manifold	Pipe T-1070	Manifold				
Track layout/traction	technical <input type="radio"/> low <input type="radio"/> mixed <input checked="" type="radio"/> medium <input checked="" type="radio"/> fast <input type="radio"/> high <input type="radio"/>	Rear φ	left 66	right 66	Bell axial play (mm)	0.2	Rear shocks		Gear ratio chart						
		Differential		Gearing		Piston	Φ1.1x2	Spur Pinion		1st 2nd					
		Front diff. oil cst.	Ride putty 45 or #1,000,000		1st gear	15 / 54	Oil	#600	14	52	53	54	47	48	49
		Rear diff. oil cst.	#50,000		2n gear	20 / 48	Spring	Xray Light Purple	15	7,614	7,761	7,907			
										19			5,071	5,179	5,278
										20			4,818	4,92	5,023
										21			4,588	4,686	4,783

