



		Tires		Clutch settings		Front shocks		Engine		
Date/Track	RC Stage Excellent	Front shore	left ZAC ZBB - / right 813CSH	Shoe/Bell	Std. / Std.	Piston	φ1.3x1	Type	OS 12XZ Speed Spec III	
Driver	Takaaki Shimo	Rear shore	left ZAC ZBB - / right 913 SH	Bell clearance (mm)	0.5	Oil	#600	Plug/Fuel	Plug RP6 / Fuel COSMO	
Temp. °C.	air / track	Front φ	left 62 / right 62	Spring/adj. Nut(mm)	Std. / 0	Spring	Mugen Purple	Pipe/Manifold	Pipe T-1070 / Manifold	
		Rear φ	left 64 / right 64	Bell axial play (mm)	0.2					
								Rear shocks	Gear ratio chart	
Track layout/traction	technical <input type="radio"/> low <input type="radio"/>	Differential		Gearing		Piston	φ1.1x2	Spur Pinion	1st	2nd
	mixed <input checked="" type="radio"/> medium <input type="radio"/>	Front diff. oil cst.	#1,000,000	1st gear	15 / 54	Oil	#600	1st	52 53 54	47 48 49
	fast <input type="radio"/> high <input checked="" type="radio"/>	Rear diff. oil cst.	#50,000	2n gear	20 / 48	Spring	Mugen Purple	2nd	14 15 19 20 21	7,614 7,761 7,907 7,107 7,243 7,38 5,071 5,179 5,278 4,818 4,92 5,023 4,588 4,686 4,783

