



		Tires		Clutch settings		Front shocks		Engine							
Date/Track	12/14/2014 PGTC Rd.5 CRP Wakayama	Front shore	left ZAC ZBB - / right 812CSH	Shoe/Bell	Std. / Std.	Piston	φ1.3x1	Type	Novarossi Virtus12						
Driver	Takehiro Terauchi	Rear shore	left ZAC ZBB - / right 9121 SH	Bell clearance (mm)	0.5	Oil	#500	Plug/Fuel	Plug C6TGF / Fuel NASA						
Temp. °C.	air 5 / track	Front φ	left 63 / right 63	Spring/adj. Nut(mm)	Std. / 0	Spring	Purple	Pipe/Manifold	Pipe 2660 / Manifold S						
Track layout/traction	technical <input type="radio"/> low <input type="radio"/> mixed <input checked="" type="radio"/> medium <input checked="" type="radio"/> fast <input type="radio"/> high <input type="radio"/>	Rear φ	left 65 / right 65	Bell axial play (mm)	0.2	Rear shocks		Gear ratio chart							
		Differential		Gearing		Piston	φ1.1x2	Spur Pinion	1st	2nd					
		Front diff. oil cst.		Ride putty 45		1st gear	15 / 54	Oil	#500						
		Rear diff. oil cst.		#50,000		2n gear	20 / 48	Spring	Purple						
									52	53	54	47	48	49	
									14	7,614	7,761	7,907			
									15	7,107	7,243	7,38			
									19				5,071	5,179	5,278
									20				4,818	4,92	5,023
									21				4,588	4,686	4,783

