



		Tires		Clutch settings		Front shocks		Engine		
Date/Track	2018-04-22 STEEL CITY SPEEDWAY USA	Front shore	left 35 / right 35	Shoe/Bell	STD / ALU	Piston	1.1X3	Type	O.S T1202	
Driver	JJ WANG	Rear shore	left 40 / right 40	Bell clearance (mm)		Oil	1000	Plug/Fuel	Plug RP6 GOLD / Fuel	
Temp. °C.	air 28 / track	Front ∅	left 60 / right 60	Spring/adj. Nut(mm)	STD /	Spring	SERPENT ORANGE	Pipe/Manifold	Pipe O.S / Manifold O.S	
Track layout/traction	technical <input type="radio"/> low <input type="radio"/> mixed <input type="radio"/> medium <input checked="" type="radio"/> fast <input checked="" type="radio"/> high <input checked="" type="radio"/>	Rear ∅	left 62 / right 62	Bell axial play (mm)		Rear shocks		Gear ratio chart		
		Differential		Gearing		Piston	1.1X3	Spur Pinion	1st	2nd
		Front diff. oil cst.	50000	1st gear	53 / 15	Oil	1000	1st	52 53 54	47 48 49
		Rear diff. oil cst.	80000	2n gear	48 / 20	Spring	SERPENT ORANGE	2nd	7,614 7,761 7,907	5,071 5,179 5,278
									7,107 7,243 7,38	4,818 4,92 5,023
										4,588 4,686 4,783

