



		Tires		Clutch settings		Front shocks		Engine				
Date/Track	2017/8/6 / 2 in 1	Front shore	left 101 Racing / right Hand out	Shoe/Bell	Std. / T2722	Piston	φ1.1x3	Type	OS Speed T1202			
Driver	Syoki Takahata	Rear shore	left 101 Racing / right Hand out	Bell clearance (mm)	0.4	Oil	#800	Plug/Fuel	Plug P5 / Fuel NASA			
Temp. °C.	air / track	Front φ	left 62 / right 62	Spring/adj. Nut(mm)	H0767 / 0.3	Spring	Serpent Orange	Pipe/Manifold	Pipe T-1070 / Manifold			
Track layout/traction	technical <input checked="" type="radio"/> low <input type="radio"/> mixed <input type="radio"/> medium <input checked="" type="radio"/> fast <input type="radio"/> high <input type="radio"/>	Rear φ	left 64 / right 64	Bell axial play (mm)	0.1	Rear shocks		Gear ratio chart				
		Differential		Gearing		Piston	φ1.1x3	Spur Pinion	1st		2nd	
		Front diff. oil cst.	#1,000,000	1st gear	14 / 54	Oil	#800	1st	14 15 19	52 7,614 7,107	53 7,761 7,243	54 7,907 7,38
		Rear diff. oil cst.	#50,000	2n gear	19 / 49	Spring	Serpent Orange (For front)	2nd	20 21	5,071 4,818		5,179 4,92 5,278 4,686
										4,588	4,686	4,783

