



		Tires		Clutch settings		Front shocks		Engine		
Date/Track	2016/9/11 / 2 in 1	Front shore	left ZAC 813 / right ZAC 813	Shoe/Bell	Std. / T2722	Piston	φ1.1x2	Type	OS Speed T1202	
Driver	Takaaki Shimo	Rear shore	left ZAC 37° / right ZAC 37°	Bell clearance (mm)	0.5	Oil	#600	Plug/Fuel	Plug P4 / Fuel Nitro-X	
Temp. °C.	air / track	Front φ	left 62 / right 62	Spring/adj. Nut(mm)	Std. / 0.2	Spring	SMJ Short Silver	Pipe/Manifold	Pipe T-1070 / Manifold	
Track layout/traction	technical <input checked="" type="radio"/> low <input checked="" type="radio"/> mixed <input type="radio"/> medium <input type="radio"/> fast <input type="radio"/> high <input type="radio"/>	Rear φ	left 64 / right 64	Bell axial play (mm)	0.1	Rear shocks		Gear ratio chart		
		Differential		Gearing		Piston	φ1.1x2	Spur Pinion		
		Front diff. oil cst.	#1,000,000	1st gear	14 / 53	Oil	#600	1st	14 7,614 7,761 7,907	2nd 47 48 49
		Rear diff. oil cst.	#60,000	2n gear	19 / 49	Spring	SMJ Long Silver	1st	15 7,107 7,243 7,38	
								2nd	19 5,071 5,179 5,278	
								2nd	20 4,818 4,92 5,023	
								2nd	21 4,588 4,686 4,783	

