

		Track		Clutch settings			Front shocks		Front anti roll bar		Engine	
Date	Layout	technical <input type="radio"/>	mixed <input checked="" type="radio"/>	fast <input type="radio"/>	Shoe	standard <input checked="" type="radio"/>	optional <input type="radio"/>	Piston	1	<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>	Type	
	Traction	low <input type="radio"/> medium <input checked="" type="radio"/> high <input type="radio"/>		Bell clearance (mm)	0,6		oil	600		<input type="radio"/> <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/>	Plug	
Driver	Temperature	air:	track:	Spring	super hard (H0767)		Spring	white		Servosaver position		Manifold
	Pinion	1st: 16	2nd: 20	Bell axial play (mm)	0,1		Rear shocks				Pipe	
Spur	1st: 49	2nd: 46	Body	Piston		2		Tires				
Race	Pulley	28 <input type="radio"/>	29 <input checked="" type="radio"/>	Type	P909		oil	600		Front	inside outside	
	Clutch	standard <input checked="" type="radio"/>	optional <input type="radio"/>	Wing position (mm)	10		Spring	white		Rear	inside outside	

