

		Track		Clutch settings			Front shocks		Front anti roll bar		Engine				
		Layout		technical <input type="radio"/>	mixed <input type="radio"/>	fast <input type="radio"/>	Shoe	standard <input checked="" type="radio"/>	optional <input type="radio"/>	Piston	1.1x1	<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>	Type		
Date			Traction		low <input type="radio"/> medium <input type="radio"/> high <input type="radio"/>		Bell clearance (mm)		0.5	Oil	600	<input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>	Plug		
			Temperature		air:	track:	Spring		H0767	Spring	White	Servosaver position		Manifold	
Driver			Pinion		1st: 16	2nd: 20	Bell axial play (mm)			Rear shocks				Pipe	
			Spur		1st: 49	2nd: 46	Body			Piston	1.1x2			Tires	
Race			Pulley		28 <input type="radio"/>	29 <input checked="" type="radio"/>	Type			Oil	600	Front		inside outside	
			Clutch		standard <input checked="" type="radio"/>	optional <input type="radio"/>	Wing position (mm)			Spring	White	Rear		inside outside	

