

| | | Track | | Clutch settings | | | Front shocks | | Front anti roll bar | | Engine | |
|--------|-------------|--|--|----------------------------|-------|---|--------------------------------|--------|---------------------|--|-------------------|--|
| Date | Layout | technical <input type="radio"/> | mixed <input checked="" type="radio"/> | fast <input type="radio"/> | Shoe | standard <input checked="" type="radio"/> | optional <input type="radio"/> | Piston | 1.1x1 | <input type="radio"/> <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> | Type | |
| | Traction | low <input type="radio"/> medium <input checked="" type="radio"/> high <input type="radio"/> | | Bell clearance (mm) | 0.6 | | Oil | 600 | | <input type="radio"/> <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> | Plug | |
| Driver | Temperature | air: | track: | Spring | H0767 | | Spring | White | | Servosaver position | Manifold | |
| | Pinion | 1st: 16 | 2nd: 20 | Bell axial play (mm) | 0.1 | | Rear shocks | | | Pipe | | |
| Race | Spur | 1st: 49 | 2nd: 46 | Body | | | Piston | 1.1x2 | | Tires | | |
| | Pulley | 28 <input type="radio"/> | 29 <input checked="" type="radio"/> | Type | P909 | | Oil | 600 | | Front | inside outside | |
| | Clutch | standard <input checked="" type="radio"/> | optional <input type="radio"/> | Wing position (mm) | 5 | | Spring | White | | Rear | inside outside | |

