



		Tires		Clutch settings		Front shocks		Engine								
Date/Track		Front shore	left 32 / right 32	Shoe / Bell	kit / kit	Piston	1 standard	Type								
Driver		Rear shore	left 35 / right 35	Bell clearance (mm)	0,6	Oil	600	Plug/Fuel	Plug	Fuel						
Temp. °C.	air / track	Front φ	left 68 / right 68	Spring/adj. Nut(mm)	kit / 0,1-0,2	Spring	white	Pipe/Manifold	Pipe	Manifold						
		Rear φ	left 75 / right 75	Bell axial play (mm)	0,1-0,2	Rear shocks		Gear ratio chart								
Track layout/traction	technical <input type="radio"/> low <input type="radio"/>	Body		Gearing		Piston	2 standard			1st	2nd					
	mixed <input checked="" type="radio"/> medium <input checked="" type="radio"/>	Type			1st gear	16 / 49	Oil	600	1st	16	48	49	50	45	46	47
	fast <input type="radio"/> high <input type="radio"/>	Wing position (mm)	8	2n gear	20 / 46	Spring	white	2nd	17	7,2	7,35	7,5				
									19	6,776	6,918	7,059	5,684	5,811	5,937	
									20				5,4	5,52	5,64	
									21				5,143	5,257	5,371	

