

DRIVER	Kit Std. Setup EU (asphalt)		
DATE			
TRACK	Carpet <input type="radio"/> Asphalt <input checked="" type="radio"/>	Arena33	
TRACTION	LOW <input type="radio"/> MEDIUM <input checked="" type="radio"/> HIGH <input type="radio"/>		
LAYOUT	SLOW <input type="radio"/> MIXED <input checked="" type="radio"/> FAST <input type="radio"/>		
TEMP °C	AIR	TRACK	
ELECTRONICS			
ESC	ESC SET	MOTOR	
SERVO	RECEIVER	BATTERY	
TIRES			
BRAND	Volante		
TYPE	V8		
ADDITIVE	MR33		
WARMER °C	FRONT 70°	REAR	70°
TIME(min)	FRONT 15	REAR	15
SHOCK ABSORBERS			
PISTON	FRONT Kit	REAR	Kit
SHOCK CASE	FRONT Kit	REAR	Kit
OIL	FRONT 400	REAR	400
SPRING	FRONT 6.5	REAR	6.25
ANTI ROLL BAR FRONT/REAR			
<input type="radio"/> 1,0 <input checked="" type="radio"/> 1,1 <input type="radio"/> 1,2			
REAR DIFFERENTIAL			
DIFF OIL CST (1,6g oil qty.)	6000		
GEAR RATIO (T)Spur/(T)Pinion*1,9=Ratio			
PINION		SPUR	
AERODYNAMIC SETTINGS			
BODY TYPE	Twister		
WING TYPE	Twister		
WING POS	(mm)	neutral	
BODY POSITION (see picture below)	(mm) \leftrightarrow horizontal	52,5	
FRONT BODY HEIGHT & POSITION	REAR BODY POST A2407C	<input checked="" type="radio"/> REAR BODY POST A2416B	<input type="radio"/>
(mm) vertical \updownarrow	47	(mm)	48

FRONT

STEERING LIMITER
 A2304 (5mm) A2305 (5.5mm) A2306 (6mm)

STEERING ANGLE IN° **ap.24**

STEERING ANGLE OUT° **17.5**

A2421 USED
 YES NO

A2421 SHIM(mm) **0**

UPPER ARM POS. FR(mm) **2.5**

FF(mm) **2.5**

LOWER ARM POS. FR(mm) **1**

FF(mm) **0**

SHOCK POS (mm) **2**

STEERING ROD POS (mm) **4**

SHIM UPRIGHT T (mm) **2**

SHIM UPRIGHT L (mm) **0.5**

UPPERARM POS. (CASTER) REAR/5° FRONT/4°

CAMBER/° **2**

TOE OUT/° **1**

OFFSET (mm) **4**

RIDE HEIGHT(mm) **5**

DOWNSTOP(mm) **6**

REAR

ACKERMANN SHIM (mm) **2**

SHIM S HORN (mm) **6**

TYPE SERVO HORN

A2529 POSITION INSIDE OUTSIDE

A2530 POSITION INSIDE OUTSIDE

REAR TOE ROD POS FRONT REAR

UPPERARM POS. (CASTER) FRONT/+4° REAR/-3°

SHIM UPRIGHT T (mm) **2**

CAMBER/° **2**

TOE IN/° **2.75**

OFFSET (mm) **4.5**

RIDE HEIGHT(mm) **5.5**

DOWNSTOP(mm) **4.6**

BATTERY POSITION FRONT REAR

CHASSIS TYPE **A2414**

MM SCREW

FRONT/REAR WEIGHT DISTRIBUTION HOLE# 1 2 3 4 5 **4**

OPTIONAL WEIGHT A2422(10g)

A2424

A2425

A2705

A2706

BELT TENSION

FRONT POS. **2**

REAR POS. **2**

A2419 SCREW

1pc. UPPERDECK TYPE 2pc. UPPERDECK TYPE

Kit

UPPERDECK SCREW

A2158

REMARKS
 -ETS body height rule