



		Tires		Clutch settings		Front shocks		Engine						
		Front shore	left / right	Shoe/Bell	Std. / Std.	Piston	φ1.1x1	Type						
Date/Track		Rear shore	left / right	Bell clearance (mm)	0.5	Oil	#600	Plug/Fuel	Plug	Fuel				
Driver		Front φ	62 / 62	Spring/adj. Nut(mm)	Std. / 0	Spring	Std.	Pipe/Manifold	Pipe	Manifold				
Temp. °C.	air / track	Rear φ	64 / 64	Bell axial play (mm)	0.2	Rear shocks		Gear ratio chart						
Track layout/traction	technical <input type="radio"/> low <input type="radio"/>	Differential		Gearing		Piston	φ1.1x2	Spur Pinion	1st		2nd			
	mixed <input type="radio"/> medium <input type="radio"/>	Front diff. oil cst.	#1,000,000	1st gear	15 / 53	Oil	#600	14	52	53	54	47	48	49
	fast <input type="radio"/> high <input type="radio"/>	Rear diff. oil cst.	#50,000	2n gear	20 / 48	Spring	Std.	15	7,614	7,761	7,907			
								19				5,071	5,179	5,278
								20				4,818	4,92	5,023
								21				4,588	4,686	4,783

