UND SCALE GAS POWERED AND TOURING CAR	Set Up Shee					MUGEN SEIKI
	Ver. 0201	Track Conditior				
Name:		Size:		Open	□ Med.	□ Tight
Date:		Tractio		•	□ Med.	□ Low
Track:		Surface	∋: □	Smooth	□ Med.	Bumpy
Front suspension					Front shocks	
	- Track		mm		Piston	
		Ride height mm			Oil #	
					Spring	l
		Caster angle mm Toe angle °			Shock position	
_		Rebound stop mm				
	Bump				/	
		None 🗆 l	Jse			£/
	Anti-ro	oll bar 💥				
		2 1 0			Front diff.	
TI CONTRACTOR					🗆 Gear d	diff.
	Steer	ring Ackerman (1	0304)		Oil	#
1000 h 0			D C		🗆 One w	/ay
Deerenereien					Deersheeke	-
Rear suspension	_ Track	width	mm		Rear shocks Piston	
	Ride h		_ ''''' 		Oil	#
		Camber angle °			Spring	
		Toe angle °				
U COM BO Les	🖞 🛛 Rebou	Rebound stop mm			Shock	position
<	A Bump	Bump stop				
5/0-2		□ None □ Use				
		Lower arm position (T0128,T0129)			\ (₹□
10 10 10		4mm(A-A) □ 5mm(B-B) □ 6mm(C-C) Anti-roll bar mm			`	
		mm				
		`				
Upper arm position	11-0 8	a 🗼	mm			
					Rear diff.	
ool [Oil	#
		1 \				
Engine				Clutch		
Type Gasket mm Muffler					Clutch shoes Black	
Plug				Spring		
	Fuel			1		
Tire Front	Rear				Clutch bell clearar	
Type					Spring Adj. Nut po	sitionmm
Dia.(start) <u>L</u> /F Dia.(finish) L/F		· · ·				
· · · · ·	Dia.(fi	,	<u> </u>			
Body		Drive ratio			Brake pad	
Туре		1st		<u>/</u>	Black	□ Yellow
Wing		2nd _		<u> </u>		
Result	Com	ments:				
Race time / Lap						
Best lap (1Lap)	I					
	11					